

RUBBER DAMPERS ACC-5220



Natural Frequency: 15 a 20 Hz.

APPLICATIONS

Damper rubber with washers for the suspension of machines with speeds from 900 rpm, motors, fans, pumps, air conditioning, compressors, marine and military, etc. Improves acoustic signature and protects against shocks.

DESCRIPTION

- Stainless steel metal parts.
- Material 30g's, depending on the static charge.
- Maximum deformation in the axial 8 mm and radial 5 mm.
- Composed of:
 - 2 elastomer washers.
 - 1 metal washer, shock function.
 - 1 connecting flange in stainless steel.

DIMENSIONAL FEATURES

Part	Nomianl Load (daN)	ØA (mm)	ØB (mm)	ØC (mm)	ØD (mm)	E (mm)	P (mm)	H clear (mm)	h under load (mm)
ACC-5224-01	14	28	28x28	20	8.2	2.5	10	42.5	35.5
ACC-5224-02	18	28	28	20	8.2	2.5	10	42.5	35.5
ACC-5225-01	27	28	28	20	8.2	2.5	10	42.5	35.5
ACC-5226-01	40	42.5	42.5	29	14.2	5	15	50	44
ACC-5226-02	60	42.5	42.5	29	14.2	5	15	50	44
ACC-5226-03	85	42.5	42.5	29	14.2	5	15	50	44
ACC-5227-01	125	56	56	35	18.2	8	15	53	47
ACC-5227-02	140	56	56	35	18.2	8	15	53	47
ACC-5227-03	185	56	56	35	18.2	8	15	53	47
ACC-5228-01	260	80	78	50	24.5	12	25	67	60.5
ACC-5228-02	320	80	78	50	24.5	12	25	67	60.5
ACC-5228-03	380	80	78	50	24.5	12	25	67	60.5
ACC-5229-01	520	90	88	53	27.5	16	25	71	64.5

